



# CELLO PRODUCTS




Copper x Female Dielectric Union

Description	Leaded PN	No Lead PN
1/2 cxf	UN-IFX-08	UNNL-IFX-08
1/2 c x 3/4 f	UN-IFXC-12-08	UNNL-IFXC-12-08
3/4 cxf	UN-IFX-12	UNNL-IFX-12
1" cxf	UN-IFX-16	UNNL-IFX-16
1-1/4 cxf	UN-IFX-20	UNNL-IFX-16
1-1/2" cxf	UN-IFX-24	UNNL-IFX-24
2" cxf	UN-IFX-32	UNNL-IFX-32




Copper x Male Dielectric Union

Description	Leaded PN	No Lead Pn
1/2 cxm	UN-IFB-08	UNNL-IFB-08
3/4 cxm	UN-IFB-12	UNNL-IFB-12



Female x Copper Flanged Dielectric Union

Description	Leaded PN	No Lead PN
2-1/2" cxf	UN-IGX-40	UNNL-IGX-40
3" cxf	UN-IGX-48	UNNL-IGX-48



Female x Female IPS Brass Dielectric Union

Description	Leaded PN	No Lead PN
1/2 FxF	UN-IEA-08	UNNL-IEA-08
3/4 FxF	UN-IIEA-12	UNNL-IEA-12
1" FxF	UN-IEA-16	UNNL-IEA-16
1-1/2" FxF	UN-IEA-24	UNNL-IEA-24
2" FxF	UN-IEA-32	UNNL-IEA-32

## Material Specifications:

- Nut - Zinc Coated Steel ASTM A108
- Insert - Nylon
- Solder Connection - Brass ASTM B-16 / LF AB1953
- Lead Free Threaded Brass - AB1953

